

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address COMMISSIONER FOR PATENTS FO Box 1430 Alexandria, Virginia 22313-1450 www.tepto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/560,460	12/14/2005	Takeshi Kobayashi	2352.011	3037
23405 7590 04/09/2008 HESLIN ROTHENBERG FARLEY & MESITI PC			EXAMINER	
5 COLUMBIA CIRCLE			SINCLAIR, DAVID M	
ALBANY, NY 12203			ART UNIT	PAPER NUMBER
			2831	
			MAIL DATE	DELIVERY MODE
			04/09/2008	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Application No. Applicant(s) KOBAYASHI ET AL. 10/560,460 Office Action Summary Examiner Art Unit DAVID M. SINCLAIR 2831 -- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for	Reply
WHICH - Extens after S - If NO; - Failure Any re	DRIENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, HEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION. It is not a time may be available under the provision of 3 CFR 1-136(a). In no event, however, may a reply be timely filled like (5) IGCNTS from the mailing date of this communication. It (5) IGCNTS from the mailing date of this communication and the control of the control of the communication and the control of the communication and the co
Status	
1)⊠ [Responsive to communication(s) filed on <u>14 December 2005</u> .
2a)□	This action is FINAL. 2b)⊠ This action is non-final.
3)□ :	Since this application is in condition for allowance except for formal matters, prosecution as to the merits is
	closed in accordance with the practice under Ex parte Quayle, 1935 C.D. 11, 453 O.G. 213.
Dispositio	on of Claims
4)🛛 (Claim(s) <u>10-18</u> is/are pending in the application.
4	a) Of the above claim(s) is/are withdrawn from consideration.
5) 🗌 (Claim(s) is/are allowed.
6)⊠ (Claim(s) <u>10-18</u> is/are rejected.
7) 🗌 (Claim(s) is/are objected to.
8)□ (Claim(s) are subject to restriction and/or election requirement.
Application	on Papers
9)□ T	he specification is objected to by the Examiner.
10)□ T	"he drawing(s) filed on is/are: a) accepted or b) objected to by the Examiner.
,	Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
	Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
11)[T	he oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.
Priority u	nder 35 U.S.C. § 119
12)🖾 A	acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
a)[∑	☑ All b) ☐ Some * c) ☐ None of:
	1.☑ Certified copies of the priority documents have been received.
	 Certified copies of the priority documents have been received in Application No
	3. Copies of the certified copies of the priority documents have been received in this National Stage
	application from the International Bureau (PCT Rule 17.2(a)).
* Se	ee the attached detailed Office action for a list of the certified copies not received.
Attachment/	(e)

1) Notice of References Cited (PTO-892) 4) Interview Summary (PTO-413) Paper No(s)/Mail Date. Notice of Draftsperson's Patent Drawing Review (PTO-948)
 Information Disclosure Statement(s) (PTO/S5/08) 5) Notice of Informal Patent Application Paper No(s)/Mail Date 12/14/2005 & 3/30/2006. 6) Other: ___ PTOL-326 (Rev. 08-06) Part of Paper No./Mail Date 20080327 Office Action Summary

Application/Control Number: 10/560,460 Page 2

Art Unit: 2831

DETAILED ACTION

Claim Rejections - 35 USC § 103

 The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

- The factual inquiries set forth in *Graham* v. *John Deere Co.*, 383 U.S. 1, 148
 USPQ 459 (1966), that are applied for establishing a background for determining obviousness under 35 U.S.C. 103(a) are summarized as follows:
 - Determining the scope and contents of the prior art.
 - 2. Ascertaining the differences between the prior art and the claims at issue.
 - Resolving the level of ordinary skill in the pertinent art.
 - Considering objective evidence present in the application indicating obviousness or nonobviousness.
- Claims 10-13 and 16-17 are rejected under 35 U.S.C. 103(a) as being unpatentable over JP 3-361563 hereafter referred to as JP563 in view of Takase '876. In regards to claim 10,

JP563 discloses a separator for an electric double layer capacitor, wherein a layer of an ultrafine fibrous aggregate prepared by an electrostatic spinning process is contained, an average fiber diameter of ultrafine fibers constituting said ultrafine fibrous aggregate layer is 1 µm or less (abstract; page 2 – right column – lines 5-16 and left column – line 5: page 14 right column line 12).

Art Unit: 2831

JP563 fails to teach the separator for an electric double layer capacitor, the thickness of the entire separator is 25 µm or less, and a maximum pore size of said ultrafine aggregate is not more than 3 times a mean flow pore size.

Takase '876 teaches a separator wherein the thickness of the entire separator is 25 µm or less ([0057]) and a maximum pore size of said ultrafine aggregate is not more than 3 times a mean flow pore size ([0071]). Takase '876 fails to teach the separator for an electric double layer capacitor.

It would have been obvious to one of ordinary skill in the art at the time the invention was made to use the thickness and ratio taught by Takase '876 with the separator of JP563 to obtain a separator that is small in size and has a narrow distribution of pore size which allows the electrolyte to be uniformly dispersed thus reducing the internal resistance.

The limitation "for and electric double layer capacitor" is an intended use of the separator, it has been held that a recitation with respect to the manner in which a claimed apparatus is intended to be employed does not differentiate the claimed apparatus from a prior art apparatus satisfying the claimed structural limitations. Ex parte Masham, 2 USPQ2d 1647 (1987)

In regards to claim 11,

The references as applied above disclose all the limitations of claim 11 except a thickness of the entire separator is 20 µm or less.

Takase '876 teaches a thickness of the entire separator is 20 μm or less ([0057]).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to use the thickness taught by Takase '876 with the separator of JP563 to obtain a separator that is small in size allowing miniaturization of the device it is used in.

In regards to claim 12,

The references as applied above disclose all the limitations of claim 12 except the mean flow pore size of said ultrafine fibrous aggregate layer is 1 µm or less.

Takase '876 teaches mean flow pore size of said ultrafine fibrous aggregate layer is 1 μ m or less ([0091] – maximum pore size is 40 μ m or less therefore mean flow pore size is 20 μ m or less).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to use the mean flow pore size taught by Takase '876 with

the separator of JP563 to obtain a separator that allows uniform dispersion of an electrolyte.

In regards to claim 13,

The references as applied above disclose all the limitations of claim 13 except a ratio (Dd/Da) of a standard deviation (Dd) of fiber diameters of ultrafine fibers constituting said ultrafine fibrous aggregate layer to an average fiber diameter (Da) of ultrafine fibers constituting said ultrafine fibrous aggregate layer is 0.25 or less

Takase '876 teaches a ratio (Dd/Da) of a standard deviation (Dd) of fiber diameters of ultrafine fibers constituting said ultrafine fibrous aggregate layer to an average fiber diameter (Da) of ultrafine fibers constituting said ultrafine fibrous aggregate layer is 0.25 or less (100251).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to use the ratio taught by Takase '876 with the separator of JP563 to obtain a separator with uniform pore diameter and internal space allowing the electrolyte to be uniformly distributed.

In regards to claim 16,

The references as applied above disclose all the limitations of claim 16 except a porosity of said separator is 50% to 95%.

Takase '867 teaches a porosity of said separator is 50% to 95% ([0072]).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to use the porosity taught by Takase '876 with the separator of JP563 to obtain a separator with lowered internal resistance and pressure.

In regards to claim 17,

The references as applied above disclose all the limitations of claim 17 except a tensile strength per 1 g/m^2 in mass per unit area is 0.15 N/5 mm width or more in at least one direction of said separator

Takase '867 teaches a tensile strength per 1 g/m² in mass per unit area is 0.15 N/5 mm width or more in at least one direction of said separator ([0075]).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to use the tensile strength taught by Takase '876 with the separator of JP563 to obtain a separator that is less susceptible to breakage.

Application/Control Number: 10/560,460 Page 7

Art Unit: 2831

 Claim 14 is rejected under 35 U.S.C. 103(a) as being unpatentable over JP563 and Takase '876 as applied to claim 10 above, and further in view of Thrasher et al. (2003/0086171).

The references as applied above disclose all the limitations of claim 14 except said ultrafine fiber is composed of at least one resin selected from the group consisting of polyacrylonitrile, polyvinylidene fluoride, polywinde, nylon, polystyrene, polyethylene glycol, polyvinyl alcohol, and polyvinyl pyrrolidone.

Thrasher '171 teaches a separator comprising fibers composed of at least one resin selected from the group consisting of polyacrylonitrile, polyvinylidene fluoride, polyimide, nylon, polystyrene, polyethylene glycol, polyvinyl alcohol, and polyvinyl pyrrolidone ([0017]).

It would have been obvious to one having ordinary skill in the art at the time the invention was made to use at least one material resin material selected from the group consisting of polyacrylonitrile, polyvinylidene fluoride, polyimide, nylon, polystyrene, polyethylene glycol, polyvinyl alcohol, and polyvinyl pyrrolidone to form the ultrafine fibers, since it has been held to be within the general skill of a worker in the art to select a known material on the basis of its suitability for the intended use as a matter of obvious design choice. In re Leshin, 125 USPQ 416. ((0057)).

Application/Control Number: 10/560,460 Page 8

Art Unit: 2831

5. Claim 18 is rejected under 35 U.S.C. 103(a) as being unpatentable over

Watanabe et al. (4,697,224) in view of JP563 and Takase '876.

Watanabe '224 discloses a double layer capacitor comprising a separator

(abstract). Watanabe fails to teach the separator according to claim 10.

The combination of claim 10 teaches the separator according to claim 10 (see

rejection above).

It would have been obvious to one of ordinary skill in the art at the time the

invention was made to use the separator taught by the combination with the

electric double layer capacitor of Watanabe '224 to obtain an electric double

layer capacitor comprising a separator having a good electrolyte holding

capacity.

6. Claims 10-14 & 16-17 are rejected under 35 U.S.C. 103(a) as being unpatentable

over Arora et al. (7,112,389) in view of Takase '876.

In regards to claim 10.

Arora '389 discloses a separator (abstract) for an electric double layer capacitor,

wherein a thickness of the entire separator is 25 µm or less (column 3 – lines 28-

39), a layer of an ultrafine fibrous aggregate prepared by an electrostatic

spinning process is contained (column 10 - lines 12-40), an average fiber

diameter of ultrafine fibers constituting said ultrafine fibrous aggregate layer is 1

µm or less (column 3 – lines 28-39). Arora '389 fails to teach the separator for an electric double layer capacitor, a maximum pore size of said ultrafine fibrous aggregate is not more than 3 times a mean flow pore size.

Takase '876 teaches a maximum pore size of said ultrafine fibrous aggregate is not more than 3 times a mean flow pore size ([0071]). Takase '876 fails to teach the separator for an electric double layer capacitor.

It would have been obvious to one of ordinary skill in the art at the time of the invention to use the ratio taught by Takase '876 with the separator of Arora '389 to obtain a separator with a narrow distribution of pore size which allows the electrolyte to be uniformly dispersed thus reducing the internal resistance.

The limitation "for and electric double layer capacitor" is an intended use of the separator, it has been held that a recitation with respect to the manner in which a claimed apparatus is intended to be employed does not differentiate the claimed apparatus from a prior art apparatus satisfying the claimed structural limitations.

Ex parte Masham, 2 USPQ2d 1647 (1987)

In regards to claim 11,

Art Unit: 2831

The references as applied above disclose all the limitations of claim 11 except a thickness of the entire separator is 20 µm or less. However, Arora '389 further teaches a thickness of the entire separator is 20 µm or less (example 11).

In regards to claim 12.

The references as applied above disclose all the limitations of claim 12 except said mean flow pore size of said ultrafine fibrous aggregate layer is 1 μ m or less. However, Arora '389 further teaches said mean flow pore size of said ultrafine fibrous aggregate layer is 1 μ m or less (examples 11-13).

In regards to claim 13,

The references as applied above disclose all the limitations of claim 13 except a ratio (Dd/Da) of a standard deviation (Dd) of fiber diameters of ultrafine fibers constituting said ultrafine fibrous aggregate layer to an average fiber diameter (Da) of ultrafine fibers constituting said ultrafine fibrous aggregate layer is 0.25 or less.

Takase '876 teaches a ratio (Dd/Da) of a standard deviation (Dd) of fiber diameters of ultrafine fibers constituting said ultrafine fibrous aggregate layer to an average fiber diameter (Da) of ultrafine fibers constituting said ultrafine fibrous aggregate layer is 0.25 or less (f00251).

Art Unit: 2831

It would have been obvious to one of ordinary skill in the art at the time the

invention was made to use the ratio taught by Takase '876 with the separator of

Arora '389 to obtain a separator with uniform pore diameter and internal space

allowing the electrolyte to be uniformly distributed.

In regards to claim 14,

The references as applied above disclose all the limitations of claim 14 except

said ultrafine fiber is composed of at least one resin selected from the group

consisting of polyacrylonitrile, polyvinylidene fluoride, polyimide, nylon,

polystyrene, polyethylene glycol, polyvinyl alcohol, and polyvinyl pyrrolidone.

However, Arora '389 further teaches said ultrafine fiber is composed of at least

one resin selected from the group consisting of polyacrylonitrile, polyvinylidene

fluoride, polyimide, nylon, polystyrene, polyethylene glycol, polyvinyl alcohol, and

polyvinyl pyrrolidone (column 4 – line 62 to column 5 – line 6).

In regards to claim 16,

The references as applied above disclose all the limitations of claim 16 except a

porosity of said separator is 50% to 95% However, Arora '389 further teaches a

porosity of said separator is 50% to 95% (column 3 – lines 28-39).

In regards to claim 17.

Art Unit: 2831

The references as applied above disclose all the limitations of claim 17 except a tensile strength per 1 g/m² in mass per unit area is 0.15 N/5 mm width or more in at least one direction of said separator

Takase '867 teaches a tensile strength per 1 g/m² in mass per unit area is 0.15 N/5 mm width or more in at least one direction of said separator ([0075]).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to use the tensile strength taught by Takase '876 with the separator of JP563 to obtain a separator that is less susceptible to breakage.

 Claims 10 & 15 are rejected under 35 U.S.C. 103(a) as being unpatentable overJP563 in view of Machine translation of JP2003-105660 hereafter referred to as JP660.

In regards to claim 10,

JP563 discloses a separator for an electric double layer capacitor, wherein a layer of an ultrafine fibrous aggregate prepared by an electrostatic spinning process is contained, an average fiber diameter of ultrafine fibers constituting said ultrafine fibrous aggregate layer is 1 µm or less (abstract; page 2 – right column - lines 5-16 and left column – line 5; page 14 right column line 12). JP563 fails to teach the separator for an electric double layer capacitor, the

Art Unit: 2831

thickness of the entire separator is $25~\mu m$ or less, and a maximum pore size of said ultrafine aggregate is not more than 3 times a mean flow pore size.

JP660 teaches a separator for a capacitor ([claim 8]) wherein the thickness of the entire separator is 25 µm or less (claim 5) and a maximum pore size of said ultrafine aggregate is not more than 3 times a mean flow pore size (table 1).

JP660 fails to teach the separator for an electric double layer capacitor.

It would have been obvious to one of ordinary skill in the art at the time the invention was made to use the thickness and ratio taught by JP 660 with the separator of JP563 to obtain a separator that is small in size and excellent in ion conductivity.

The limitation "for and electric double layer capacitor" is an intended use of the separator, it has been held that a recitation with respect to the manner in which a claimed apparatus is intended to be employed does not differentiate the claimed apparatus from a prior art apparatus satisfying the claimed structural limitations. Ex parte Masham, 2 USPQ2d 1647 (1987)

In regards to claim 15,

The references as applied above disclose all the limitations of claim 15 except the separator containing a non-ultrafine fibrous aggregate layer having an Art Unit: 2831

average fiber diameter of not less than 1 μ m, in addition to said ultrafine fibrous aggregate layer.

JP 660 teaches the separator containing a non-ultrafine fibrous aggregate layer having an average fiber diameter of not less than 1 μ m ([0128] & [0024] – thick fiber), in addition to said ultrafine fibrous aggregate layer (super-thin fiber layer).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to use the non-ultrafine fiber layer taught by JP 660 with the separator of JP563 to obtain a separator that has improved strength.

Conclusion

 The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.

"A multi-layered approach for absorptive lass-mat separators" teaches forming a separator of a fine fiber layer and a course fiber layer to improve the strength.

Communication

Any inquiry concerning this communication or earlier communications from the examiner should be directed to DAVID M. SINCLAIR whose telephone number is (571)270-5068. The examiner can normally be reached on Mon - Thurs 6:30-5.

Art Unit: 2831

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Diego F. Gutierrez can be reached on (571) 272-2245. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/D. M. S./ Examiner, Art Unit 2831

/Eric Thomas/ Primary Examiner, Art Unit 2831